



# Aluminium Excavator Trailer

**Built tough  
High strength to weight ratio**

**Built with pride, so you can tow with trust!**

**\*ATM:** 2250Kg (GTM: 2000KG) (Tare Weight: 360kg)

**Load Area:** 2100x420 (drive up track)

**Suspension:** Parabolic Springs

**Axles:** 50sq 100 drop axle SL Bearings (Ford Stud Pattern)

**Brakes:** Disc Over-Ride (front axle braked, rear axle lazy)

**Floor:** Tracked Floor (3mm aluminium tread plate)

**Ramps:** 2x Single Ladder Style (1200X390) with fixed stabilizer

**Tyres/Rims:** New 185x14LT 8PLY with white ranger style 5 stud rims

**Spare Tyre:** (1) as above mounted

**Lights:** LED Multi Volt

**Jockey Wheel or Stand** (bolted, swing up)

**Plug:** 7 Pin round or flat

**Tie Downs:** (5) rated eye bolts



**Additional Options:**

12 months QLD Registration

Chain Restraint Kits

Electric Brakes

\*Attachment rack/mounts

(\* note this will vary the tare therefore payload capacity)

**Upgrades Available:**

ATM 2.8T or 3.5T Trailer Upgrade Available

(Inc. Suspension/Axle upgrade to rocker roller, electric brakes with breakaway system and load area)

\*Aggregated Trailer Mass

